

View Online at https://aerobasegroup.com/nsn/1670-00-600-6256

| Overall Length:         3.820 inches         Overall Height:         0.550 inches         Overall Width:         2.760 inches         Mounting Hole Diameter:         0.261 inches and 0.389 inches         Mounting Hole Diameter:         0.261 inches and 0.389 inches         Mounting Hole Type:         Plain         Ring Style:         Pear         Mounting Hole Arrangement Style:         Three hole triangular         Inside Width:         0.620 inches         Longest Horizontal Distance Between Mounting Centers:         0.800 inches         Engest Horizontal Distance Between Mounting Centers:         0.800 inches         Longest Vertical Distance Between Mounting Centers:         0.800 inches         Longest Vertical Distance Between Mounting Centers:         1.870 inches         Harinent Type:         1.870 inches         Maximum Load Rating:         1.550 inches         Material:         Steel, mil-s-6758, sae 4130 and steel         Material:         Steel comp 4130 and steel         Material:         Steel comp 4130 and steel         Material:  |  |
|--|--|
| Overall Height:0.550 inchesOverall Width:2.760 inchesMounting Hole Diameter:0.261 inches and 0.389 inchesMounting Hole Type:PlainRing Style:PlainRing Style:PearMounting Hole Arrangement Style:Three hole triangularInside Width:0.620 inchesLongest Horizontal Distance Between Mounting Centers:1.200 inchesStortest Horizontal Distance Between Mounting Centers:1.870 inchesInside Height:1.550 inchesInside Height:1.550 inchesInside Height:1.500 inchesIsteinen:1.500 inchesIsteinen:1.500 inchesInchesInside Height:1.500 inchesIsteinen:<   | Overall Length:  |
| 0.550 indes<br>Verail Width:<br>2.760 indes<br>Mounting Hole Dlameter:<br>0.261 indes and 0.389 indes<br>Mounting Hole Type:<br>Plain<br>Ring Style:<br>Pear<br>Mounting Hole Arrangement Style:<br>Three hole triangular<br>Inside Width:<br>0.620 indes<br>Longest Horizontal Distance Between Mounting Centers:<br>1.200 indes<br>Shortest Horizontal Distance Between Mounting Centers:<br>0.600 indes<br>Longest Vertical Distance Between Mounting Centers:<br>1.870 indes<br>Inside Height:<br>1.870 indes<br>Kaside Height:<br>1.850 indes<br>Maximun Load Rating:<br>1.500 indes<br>Maximun Load Ratin | 3.820 inches   |
| Overall Width:2.760 inchesMounting Hole Diameter:0.261 inches and 0.389 inchesMounting Hole Type:PlainRing Style:PearMounting Hole Arrangement Style:Three hole triangularIncide Width:0.520 inchesLongest Horizontal Distance Between Mounting Centers:1.200 inchesBongest Vertical Distance Between Mounting Centers:1.870 inchesLongest Vertical Distance Between Mounting Centers:1.870 inchesBacterine:1.800 inchesBacterine:Stellerine:Stellerine:Nateria:Stellerine:Nateria:Stellerine:Vertical Distance:Interie:Nateria:Stellerine:Nateria:Stellerine:Nateria:Stellerine:Nateria:Stellerine:   | Overall Height:  |
| 2.760 inches Mounting Hole Diameter: 0.261 inches and 0.389 inches Mounting Hole Type: Plain Plain Plai Plai Plai Three hole triangular Inside Width: 0.620 inches Longest Horizontal Distance Between Mounting Centers: 1.200 inches Longest Horizontal Distance Between Mounting Centers: 0.600 inches Longest Vertical Distance Between Mounting Centers: 1.870 inches Longest Vertical Distance Between Mounting Centers: Longest Vertical Distance Between Mounting Centers: Longest Vertical Distance Between Mounting Centers: Longest Vertical Distance Between   | 0.550 inches   |
| Mounting Hole Diameter:         0.261 inches and 0.389 inches         Mounting Hole Type:         Plain         Ring Style:         Pear         Mounting Hole Arrangement Style:         Three hole triangular         Inside Width:         0.820 inches         Longest Horizontal Distance Between Mounting Centers:         1.200 inches         Schortest Horizontal Distance Between Mounting Centers:         0.800 inches         Longest Vertical Distance Between Mounting Centers:         1.870 inches         Haximum Load Rating:         1.550 inches         Attachment Type:         Cargor ing         Material:         Steel comp 4130 and steel         Material:         Steel comp 4130 and steel         Shift Life:         Na         Via         Via Of Measure:         -         Feel miltarization:   | Overall Width:   |
| 0.261 inches and 0.389 inches         Mounting Hole Type:         Plain         Ring Style:         Pear         Mounting Hole Arrangement Style:         Three hole triangular         Inside Width:         0.620 inches         Longest Horizontal Distance Between Mounting Centers:         1.200 inches         Shortest Horizontal Distance Between Mounting Centers:         0.600 inches         Longest Vertical Distance Between Mounting Centers:         1.200 inches         Horizontal Distance Between Mounting Centers:         0.600 inches         Longest Vertical Distance Between Mounting Centers:         1.870 inches         Horizon Anterial         1.550 inches         Maximum Load Rating:         1.550 inches         Material:         Steel, mil-s-6758, sae 4130 and steel         Material:         Steel comp 4130 and steel         Shift Life:         Na         Unit Of Measure:         -         Penilitarization:         Yes - demil/mli   | 2.760 inches   |
| Mounting Hole Type:         Plain         Ring Style:         Pear         Mounting Hole Arrangement Style:         Three hole triangular         Inside Width:         0.620 inches         Longest Horizontal Distance Between Mounting Centers:         1.200 inches         Shortest Horizontal Distance Between Mounting Centers:         0.600 inches         Longest Vertical Distance Between Mounting Centers:         1.200 inches         Bortest Horizontal Distance Between Mounting Centers:         1.870 inches         Harden Type:         1.550 inches         Maximum Load Rating:         1.500 inches         Maximum Load Rating:         1.5000.0 pounds         Atachemen Type:         Cargo ring         Material:         Steel comp 4130 and steel         Material:         Na         Unit Of Measure:         va         Parieliarization:         r-         Parieliarization:  | Mounting Hole Diameter:                                |
| Plain         Ring Style:         Pear         Mounting Hole Arrangement Style:         Three hole triangular         Inside Width:         0.600 inches         Longest Horizontal Distance Between Mounting Centers:         0.600 inches         Shortest Horizontal Distance Between Mounting Centers:         0.600 inches         Longest Vertical Distance Between Mounting Centers:         1.870 inches         Haside Height:         1.550 inches         Maximum Load Rating:         1.550 inches         Maximum Load Rating:         1.550 inches         Material:         Scargor ring         Material:         Steel comp 4130 and steel         Sheft Lite:         Na         Steel Comp 4130 and steel         Sheif Lite:         Na  | 0.261 inches and 0.389 inches                          |
| Ring Style:         Pear         Mounting Hole Arrangement Style:         Three hole triangular         Inside Width:         0.620 inches         Longest Horizontal Distance Between Mounting Centers:         1.20 inches         Shortest Horizontal Distance Between Mounting Centers:         0.600 inches         Longest Vertical Distance Between Mounting Centers:         1.870 inches         Inside Height:         1.550 inches         Maximum Load Rating:         155000.0 pounds         Attachment Type:         Cargo ring         Material:         Steel comp 4130 and steel         Material:         Steel comp 4130 and steel         Material:         Na'         Unit Of Measure:         r         Paillitarization:         r         Fig:   | Mounting Hole Type:                                    |
| Pear Mounting Hole Arrangement Style: Three hole triangular Inside Width: 0.620 inches Congest Horizontal Distance Between Mounting Centers: 1.200 inches Shortest Horizontal Distance Between Mounting Centers: 0.600 inches Congest Vertical Distance Between Mounting Centers: 1.370 inches Inside Height: 1.370 inches Inside Height: 1.350 inches Material: Steel, mil-s-6758, sae 4130 and steel Material: Steel, mil-s-6758, sae 4130 and steel Material: Na  fue   | Plain  |
| Mounting Hole Arrangement Style:         Three hole triangular         Inside Width:         0.620 inches         Longest Horizontal Distance Between Mounting Centers:         1.200 inches         Shortest Horizontal Distance Between Mounting Centers:         0.600 inches         Longest Vertical Distance Between Mounting Centers:         0.800 inches         Longest Vertical Distance Between Mounting Centers:         1.870 inches         Inside Height:         1.550 inches         Maximum Load Rating:         15000.0 pounds         Attachment Type:         Cargo ring         Material:         Steel, mil-s-6758, sae 4130 and steel         Material:         Steel comp 4130 and steel         Material:         Na         Steel comp 4130 and steel         Material:         Na         Int Of Measure:         -         Pamilitarization:         -         Femilitarization:         Fig:  | Ring Style:  |
| Three hole triangular Inside Width: O.620 inches Congest Horizontal Distance Between Mounting Centers: 1.200 inches Shortest Horizontal Distance Between Mounting Centers: O.600 inches Congest Vertical Distance Between Mounting Centers: 1.870 inches Inside Height: 1.550 inches Maximum Load Rating: 1.550 inches Attachment Type: Cargo ring Material: Steel, mil-s-6758, sae 4130 and steel Material: Steel comp 4130 and steel Sheff Life: N/a Unit Of Measure: Demil/tarization: Yes - demil/mii  | Pear   |
| Inside Width:<br>0.620 inches<br>Longest Horizontal Distance Between Mounting Centers:<br>1.200 inches<br>Shortest Horizontal Distance Between Mounting Centers:<br>0.600 inches<br>Longest Vertical Distance Between Mounting Centers:<br>1.870 inches<br>Inside Height:<br>1.870 inches<br>Inside Height:<br>1.550 inches<br>Maximum Load Rating:<br>1.550 inches<br>Maximum Load Rating:<br>1.5000.0 pounds<br>Attachment Type:<br>Cargo ring<br>Material:<br>Steel, mil-s-6758, sae 4130 and steel<br>Material:<br>Steel comp 4130 and steel<br>Sheff Life:<br>N/a<br>Lint Of Measure:<br><br>Demilitarization:<br>Yes - demil/mil   | Mounting Hole Arrangement Style:                       |
| 0.620 inches         1.200 inches         Shortest Horizontal Distance Between Mounting Centers:         0.600 inches         Longest Vertical Distance Between Mounting Centers:         1.870 inches         Inside Height:         1.550 inches         Maximum Load Rating:         1.550 inches         Attachment Type:         Cargo ring         Material:         Steel comp 4130 and steel         Material:         Steel comp 4130 and steel         Material:         Init of Measure:         Init of Measure:         Imit of Measure: <tr td=""></tr>  | Three hole triangular                                  |
|  |  |
| Longest Horizontal Distance Between Mounting Centers:         1.200 inches         Shortest Horizontal Distance Between Mounting Centers:         0.600 inches         Longest Vertical Distance Between Mounting Centers:         1.870 inches         Inside Height:         1.550 inches         Maximum Load Rating:         150000.0 pounds         Attachment Type:         Cargo ring         Material:         Steel, mil-s-6758, sae 4130 and steel         Material:         Steel comp 4130 and steel         Material:         N/a         Unit of Measure:         -         Pomilitarization:         Formilitarization:   | Inside Width:  |
| 1.200 inches         Shortest Horizontal Distance Between Mounting Centers:         0.600 inches         Longest Vertical Distance Between Mounting Centers:         1.870 inches         Inside Height:         1.550 inches         Maximum Load Rating:         150000.0 pounds         Attachment Type:         Cargo ring         Material:         Steel, mil-s-6758, sae 4130 and steel         Material:         Steel comp 4130 and steel         Shelf Life:         N/a         Unit Of Measure:         -         Permilitarization:         Yes - demil/mli   | 0.620 inches   |
| Shortest Horizontal Distance Between Mounting Centers:         0.600 inches         Longest Vertical Distance Between Mounting Centers:         1.870 inches         Inside Height:         1.550 inches         Maximum Load Rating:         15000.0 pounds         Attachment Type:         Cargo ring         Material:         Steel, mil-s-6758, sae 4130 and steel         Material:         Steel comp 4130 and steel         Sheff Life:         N'a         Dirt of Measure:         -         Formiltarization:         Formiltarization:         Fig:   | Longest Horizontal Distance Between Mounting Centers:  |
| 0.600 inches Longest Vertical Distance Between Mounting Centers: 1.870 inches Inside Height: 1.570 inches Maximum Load Rating: 1.550 inches Maximum Load Rating: 150000.0 pounds Attachment Type: Cargo ring Material: Steel, mil-s-6758, sae 4130 and steel Material: Steel comp 4130 and steel Steel comp 4130 and steel Steel comp 4130 and steel N/a Unit Of Measure: Demiltarization: Yes - demil/mli Fig:  | 1.200 inches   |
| Longest Vertical Distance Between Mounting Centers:1.870 inchesInside Height:1.550 inchesMaximum Load Rating:150000.0 poundsAttachment Type:Cargo ringMaterial:Steel, mil-s-6758, sae 4130 and steelMaterial:Steel comp 4130 and steelSheff Life:N/aUnit Of Measure:-Penilitarization:Yes - demil/mliFig:  | Shortest Horizontal Distance Between Mounting Centers: |
| 1.870 inches<br>Inside Height:<br>1.550 inches<br>Maximum Load Rating:<br>150000.0 pounds<br>Attachment Type:<br>Cargo ring<br>Material:<br>Steel, mil-s-6758, sae 4130 and steel<br>Material:<br>Steel comp 4130 and steel<br>Steel comp 4130 and steel<br>Steel comp 4130 and steel<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:<br>Yes - demil/mli<br>Fiig:  | 0.600 inches   |
| Inside Height: 1.550 inches 1.550 inches Maximum Load Rating: 150000.0 pounds 150000.0 pounds Attachment Type: Cargo ring Material: Steel, mil-s-6758, sae 4130 and steel Material: Steel comp 4130 and steel Shelf Life: N/a Unit Of Measure: Immediate Steel Steel compine Steel Steel co  | Longest Vertical Distance Between Mounting Centers:    |
| 1.550 inches Maximum Load Rating: 150000.0 pounds Attachment Type: Cargo ring Material: Steel, mil-s-6758, sae 4130 and steel Material: Steel comp 4130 and steel Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:  | 1.870 inches   |
| Maximum Load Rating:150000.0 poundsAttachment Type:Cargo ringMaterial:Steel, mil-s-6758, sae 4130 and steelMaterial:Steel comp 4130 and steelSteel comp 4130 and steelShelf Life:N/aUnit Of Measure:penilitarization:Yes - demil/mliFig:   | Inside Height:   |
| 150000.0 pounds<br>Attachment Type:<br>Cargo ring<br>Material:<br>Steel, mil-s-6758, sae 4130 and steel<br>Material:<br>Steel comp 4130 and steel<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Pemilitarization:<br>Yes - demil/mli<br>Fiig:   | 1.550 inches   |
| Attachment Type:Cargo ringMaterial:Steel, mil-s-6758, sae 4130 and steelMaterial:Steel comp 4130 and steelSteel comp 4130 and steelShelf Life:N/aUnit Of Measure:Penilitarization:Yes - demil/mliFig:  | Maximum Load Rating:                                   |
| Cargo ring<br>Material:<br>Steel, mil-s-6758, sae 4130 and steel<br>Material:<br>Steel comp 4130 and steel<br>Steel comp 4130 and steel<br>Shelf Life:<br>N/a<br>Dhit Of Measure:<br><br>Formilitarization:<br>Yes - demil/mli<br>Fig:   | 150000.0 pounds  |
| Material:   Steel, mil-s-6758, sae 4130 and steel   Material:   Steel comp 4130 and steel   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   Yes - demil/mli   Fig:  | Attachment Type:                                       |
| Steel, mil-s-6758, sae 4130 and steel Material: Steel comp 4130 and steel Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:  | Cargo ring   |
| Material:Steel comp 4130 and steelShelf Life:N/aUnit Of Measure:Demilitarization:Yes - demil/mliFig:   | Material:  |
| Steel comp 4130 and steel Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:   | Steel, mil-s-6758, sae 4130 and steel                  |
| Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   Yes - demil/mli   Fiig:   | Material:  |
| N/a<br>Unit Of Measure:<br><br>Demilitarization:<br>Yes - demil/mli<br>Fiig:   | Steel comp 4130 and steel                              |
| Unit Of Measure:<br><br>Demilitarization:<br>Yes - demil/mli<br>Fiig:  | Shelf Life:  |
| <br>Demilitarization:<br>Yes - demil/mli<br>Fiig:  | N/a  |
| Yes - demil/mli<br>Fiig:   | Unit Of Measure:                                       |
| Yes - demil/mli<br>Fiig:   |  |
| Fiig:  | Demilitarization:                                      |
|  | Yes - demil/mli  |
| A30600   | Fiig:  |
|  | A30600   |
|  |  |