

View Online at <https://aerobasegroup.com/nsn/1680-00-010-9592>

Thread Class:

2b first end

Thread Direction:

Right-hand first end

Spline Major Diameter:

0.312 inches first end

Overall Length:

45.500 inches

Spline Quantity:

12 first end

Spline Minor Diameter:

0.281 inches first end

Wrenching Facility Outside Diameter:

0.875 inches second end

Thread Depth:

0.562 inches first end

Tip Length:

0.500 inches first end

Shank Outside Diameter:

0.343 inches second end

Pitch Diameter:

0.250 inches first end

Shoulder Outside Diameter:

0.875 inches second end

Core Material:

Steel

Screw Thread Series Designator:

Unf first end

Core Diameter:

0.187 inches

Thread Location:

Internal first end

End Type:

Round, internal splined first end

Width Across Flats:

0.375 inches first end

End Connection Type:

Union ferrule first end

Spline Pressure Angle In Deg:

14.5 first end

Spline Length:

0.211 inches first end

Spline Type:

Involute first end

Setscrew:

Not included second end

Casing Material:

Steel, corrosion resisting

Wrenching Facility Type:

Knurled surface second end

Cross Section Size And Location:

0.750 inches diameter second end

Casing Surface Treatment:

Passivated

Casing Length Between Ferrules:

44.063 inches

Casing Outside Diameter:

0.343 inches

Swivel End:

Provided first end

Enddiameter:

0.500 inches second end

Lubrication Fitting:

Not provided second end

Corelength:

45.500 inches

Core Rotation Direction:

Counterclockwise

Core Tip Thread Class:

2b second end

Core Tip Thread Direction:

Right-hand second end

Core Removability:

Removable

Fsc Application Data:

Pedals, control, acft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T246-e