

View Online at <https://aerobasegroup.com/nsn/1680-00-027-5747>

Thread Class:

3 both ends

Thread Direction:

Right-hand both ends

Thread Length:

1.500 inches both ends

Spline Major Diameter:

0.297 inches first end

Overall Length:

19.569 inches

Spline Quantity:

12 first end

Spline Minor Diameter:

0.235 inches first end

Wrenching Facility Outside Diameter:

0.750 inches both ends

Tip Length:

0.469 inches second end

Shank Outside Diameter:

0.406 inches both ends

Pitch Diameter:

0.250 inches first end

Shoulder Outside Diameter:

0.750 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Unef both ends

Core Diameter:

0.187 inches

Thread Location:

Internal both ends

End Type:

Threaded male second end

End Connection Type:

Threaded internal both ends

Spline Pressure Angle In Deg:

14.5 first end

Spline Length:

0.250 inches first end

Tongue Length:

0.469 inches second end

Spline Type:

Involute first end

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface both ends

Cross Section Size And Location:

0.250 inches diameter second end

Torsional Deflection Rating:

2.0 degrees ft-lb in. Torsional deflection rating for winding, 4.0 degrees ft-lb in. Torsional rating for unwinding

Casing Surface Treatment:

Zinc coated

Casing Length Between Ferrules:

18.500 inches

Casing Outside Diameter:

0.273 inches

Casing Protective Device Type:

Plastic cover

Swivel End:

Not provided both ends

Enddiameter:

1.000 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

19.469 inches

Core Rotation Direction:

Clockwise

Core Tip Thread Class:

2 second end

Core Tip Thread Direction:

Right-hand second end

Core Tip Thread Length:

0.750 inches second end

Core Removability:

Removable

Minimum Operating Radius:

3.500 inches

Special Features:

60 in.-lbs torsion strength in unwinding direction

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T246-e