

View Online at <https://aerobasegroup.com/nsn/1680-00-089-3228>

**Thread Class:**

2a both ends

**Thread Direction:**

Right-hand both ends

**Spline Major Diameter:**

0.270 inches both ends

**Overall Length:**

13.700 inches

**Spline Quantity:**

12 both ends

**Spline Minor Diameter:**

0.200 inches both ends

**Thread Depth:**

0.440 inches both ends

**Tip Length:**

0.470 inches both ends

**Shank Outside Diameter:**

0.470 inches both ends

**Pitch Diameter:**

0.250 inches both ends

**Core Material:**

Steel

**Screw Thread Series Designator:**

Uns both ends

**Core Diameter:**

0.212 inches

**Thread Location:**

Internal both ends

**End Type:**

Round, internal splined both ends

**Width Across Flats:**

0.750 inches both ends

**End Connection Type:**

Threaded internal both ends

**Spline Pressure Angle In Deg:**

14.500 both ends

**Spline Length:**

0.250 inches both ends

**Spline Type:**

Straight both ends

**Setscrew:**

Not included both ends

**Casing Material:**

Steel

**Wrenching Facility Type:**

Hexagon both ends

**Cross Section Size And Location:**

0.410 inches diameter both ends

**Torsional Deflection Rating:**

2.4 degrees ft-lb in

**Casing Surface Treatment:**

Zinc coated

**Casing Length Between Ferrules:**

12.760 inches

**Casing Outside Diameter:**

0.470 inches

**Swivel End:**

Not provided both ends

**Overall End Size:**

Both ends: 0.750 in. High

**Lubrication Fitting:**

Not provided both ends

**Corelength:**

13.700 inches

**Core Rotation Direction:**

Counterclockwise

**Core Removability:**

Nonremovable

**Minimum Operating Radius:**

3.000 inches

**Fsc Application Data:**

Actuator, electro-mech rotary

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T246-e