NSN 1680-00-165-4278

Rotary Electro-mechanical Actuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1680-00-165-4278 **Terminal Type:** Connector **Tempurature Rating:** -65.0 degrees fahrenheit and 160.0 degrees fahrenheit **Current Type:** Dc **Body Length:** 5.720 inches **Body Height:** 1.390 inches **Environmental Protection:** Dustproof and moisture proof and pressure proof and vapor **Operating Speed At Rated Capacity In Rpm:** 5.0 and 9.0 **Maximum Operating Altitude Rating:** 10000.0 feet **Shaft Rotation Direction:** Counterclockwise **Drive Type:** Direct **Duty Cycle:** Intermittent **Current Rating In Amps:** 8.0 **Braking Method:** Electric **Clutch Type:** Electromagnetic **Rotation In Deg:** Between 198.0 and 202.0 **Output Drive Torque Rating:** 20.0 foot-pounds **Limit Switch Control:** Included **Manual Override:** Not included **Angular Shaft Rotation:** Limited **Intermittent Operation Duty Cycle:** 1.0 minutes on and 5.0 minutes off Voltage In Volts:

24.0 and 28.0

NSN 1680-00-165-4278

Rotary Electro-mechanical Actuator - Page 2 of 2



Fsc	App	lication	Data:
-----	-----	----------	-------

Cargo hoist, acft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A30500