

View Online at <https://aerobasegroup.com/nsn/1680-00-211-4116>

Spline Major Diameter:

0.307 inches both ends

Overall Length:

7.061 inches

Spline Quantity:

12 both ends

Spline Minor Diameter:

0.241 inches both ends

Tip Length:

0.531 inches both ends

Shank Outside Diameter:

0.500 inches both ends

Pitch Diameter:

0.250 inches both ends

Core Material:

Steel

Core Diameter:

0.250 inches

End Type:

Round, external splined both ends

Width Across Flats:

0.750 inches both ends

End Connection Type:

Union ferrule both ends

Spline Pressure Angle In Deg:

14.5 both ends

Spline Length:

0.244 inches both ends

Spline Type:

Involute both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Hexagon both ends

Cross Section Size And Location:

0.406 inches diameter both ends

Torsional Deflection Rating:

5 degrees ft-lb in torsional deflection rating in winding direction, 7 degrees ft-lb in torsional deflection rating in unwinding direction

Casing Length Between Ferrules:

4.375 inches

Casing Outside Diameter:

0.445 inches

Swivel End:

Not provided both ends

Enddiameter:

0.875 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

7.061 inches

Core Rotation Direction:

Clockwise or counterclockwise

Core Removability:

Nonremovable

Minimum Operating Radius:

10.000 inches

Fsc Application Data:

Miscellaneous aircraft accessories and components

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T246-e