

View Online at <https://aerobasegroup.com/nsn/1680-00-309-1503>

Thread Class:

2b both ends

Thread Direction:

Right-hand both ends

Spline Major Diameter:

0.299 inches second end

Overall Length:

52.255 inches

Spline Quantity:

12 both ends

Spline Minor Diameter:

0.229 inches both ends

Wrenching Facility Outside Diameter:

0.885 inches first end

Thread Depth:

0.375 inches first end

Tip Length:

0.570 inches first end

Pitch Diameter:

0.250 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Uns both ends

Core Diameter:

0.250 inches

Thread Location:

Internal both ends

End Type:

Round, internal splined both ends

Width Across Flats:

0.750 inches second end

End Connection Type:

Threaded internal both ends

Spline Pressure Angle In Deg:

20.0 first end

Spline Length:

0.315 inches first end

Spline Type:

Involute both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface first end

Cross Section Size And Location:

0.470 inches diameter first end

Torsional Deflection Rating:

6 degrees ft-lb in.

Casing Length Between Ferrules:

50.130 inches

Casing Outside Diameter:

0.562 inches

Swivel End:

Not provided both ends

Enddiameter:

0.885 inches first end

Overall End Size:

Both ends: 0.875 in. W

Lubrication Fitting:

Not provided both ends

Corelength:

52.255 inches

Core Rotation Direction:

Clockwise or counterclockwise

Core Removability:

Nonremovable

Fsc Application Data:

Power unit actuator, acft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T246-e