

View Online at <https://aerobasegroup.com/nsn/1680-00-310-2159>

Thread Class:

2b both ends

Thread Direction:

Right-hand both ends

Thread Length:

0.437 inches both ends

Overall Length:

39.750 inches

Thread Depth:

0.437 inches both ends

Tip Length:

39.750 inches both ends

Core Material:

Steel, corrosion resisting

Screw Thread Series Designator:

Unef both ends

Core Surface Treatment:

Passivated

Core Diameter:

0.312 inches

Thread Location:

Internal both ends

End Type:

Square male both ends

Width Across Flats:

0.930 inches and 1.120 inches both ends

End Connection Type:

Threaded internal both ends

Casing Material:

Steel, corrosion resisting

Wrenching Facility Type:

Hexagon both ends

Cross Section Size And Location:

0.250 inches across flats second end

Casing Surface Treatment:

Passivated

Casing Length Between Ferrules:

38.000 inches

Casing Outside Diameter:

0.550 inches

Casing Protective Device Type:

Braided wire shield

Swivel End:

Not provided both ends

Enddiameter:

1.120 inches first end

Corelength:

38.000 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Minimum Operating Radius:

14.000 inches

Fsc Application Data:

Aircraft control assembly

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T246-e