

View Online at <https://aerobasegroup.com/nsn/1680-00-310-2159>

**Thread Class:**

2b both ends

**Thread Direction:**

Right-hand both ends

**Thread Length:**

0.437 inches both ends

**Overall Length:**

39.750 inches

**Thread Depth:**

0.437 inches both ends

**Tip Length:**

39.750 inches both ends

**Core Material:**

Steel, corrosion resisting

**Screw Thread Series Designator:**

Unef both ends

**Core Surface Treatment:**

Passivated

**Core Diameter:**

0.312 inches

**Thread Location:**

Internal both ends

**End Type:**

Square male both ends

**Width Across Flats:**

0.930 inches and 1.120 inches both ends

**End Connection Type:**

Threaded internal both ends

**Casing Material:**

Steel, corrosion resisting

**Wrenching Facility Type:**

Hexagon both ends

**Cross Section Size And Location:**

0.250 inches across flats second end

**Casing Surface Treatment:**

Passivated

**Casing Length Between Ferrules:**

38.000 inches

**Casing Outside Diameter:**

0.550 inches

**Casing Protective Device Type:**

Braided wire shield

**Swivel End:**

Not provided both ends

**Enddiameter:**

1.120 inches first end

**Corelength:**

38.000 inches

**Core Rotation Direction:**

Clockwise

**Core Removability:**

Removable

**Minimum Operating Radius:**

14.000 inches

**Fsc Application Data:**

Aircraft control assembly

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T246-e