NSN 1680-00-340-2325



Flexible Shaft Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/1680-00-340-2325 **Thread Class:** 2b both ends **Thread Direction:** Right-hand both ends Thread Length: 0.437 inches both ends **Overall Length:** 41.750 inches **Thread Depth:** 0.437 inches both ends Tip Length: 41.750 inches both ends **Core Material:** Steel, corrosion resisting **Screw Thread Series Designator:** Unef both ends **Core Surface Treatment:** Passivated

Core Diameter:

0.312 inches

Thread Location:

Internal both ends

End Type:

Square male both ends

Width Across Flats:

0.930 inches and 1.120 inches both ends

End Connection Type:

Threaded internal both ends

Casing Material:

Steel, corrosion resisting

Wrenching Facility Type:

Hexagon both ends

Casing Surface Treatment:

Passivated

Casing Length Between Ferrules:

40.500 inches

Casing Outside Diameter:

0.550 inches

Casing Protective Device Type:

Braided wire shield

Swivel End:

Provided both ends

NSN 1680-00-340-2325

Flexible Shaft Assembly - Page 2 of 2



Enddiameter:
0.930 inches and 1.120 inches both ends
Corelength:
40.500 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Minimum Operating Radius:
14.000 inches
Fsc Application Data:
Aircraft control assembly
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: T246-e