NSN 1680-00-343-3024

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1680-00-343-3024

Overall Length:
9.691 inches
Flange Thickness:
0.0652 inches both ends
Tip Length:
0.625 inches both ends
Shank Outside Diameter:
0.500 inches both ends
Core Material:
Steel
Core Diameter:
0.250 inches
End Type:
Hexagon male both ends
End Connection Type:
Union ferrule both ends
Setscrew:
Not included both ends
Casing Material:
Steel
Cross Section Size And Location:
0.225 inches diameter both ends
Torsional Deflection Rating:
5 degrees ft-lb in. Winding direction, 7 degrees in unwinding
Casing Length Between Ferrules:
9.188 inches
Casing Outside Diameter:
0.445 inches
Swivel End:
Not provided both ends
Enddiameter:
0.562 inches both ends
Lubrication Fitting:
Not provided both ends
Corelength:
8.9687 inches
Core Rotation Direction:
Clockwise or counterclockwise
Core Removability:
Nonremovable
Minimum Operating Radius:

10.000 inches

NSN 1680-00-343-3024

Flexible Shaft Assembly - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	atio	n D	ata
----------------------	-----	----	------	------	-----	-----

Miscellaneous aircraft accessories and components

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T246-e