NSN 1680-00-528-1729

Flexible Shaft Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/1680-00-528-1729



Thread Class: 2a both ends **Thread Direction:** Right-hand both ends **Spline Major Diameter:** 0.304 inches and 0.310 inches both ends **Overall Length:** 9.688 inches Spline Quantity: 12 both ends **Spline Minor Diameter:** 0.240 inches and 0.242 inches both ends **Thread Depth:** 0.219 inches both ends **Tip Length:** 0.232 inches and 0.255 inches both ends **Pitch Diameter:** 0.250 inches both ends **Core Material:** Steel **Screw Thread Series Designator:** Uns both ends **Core Diameter:** 0.250 inches **Thread Location:** Internal both ends End Type: Round, internal splined both ends Width Across Flats: 0.750 inches both ends **End Connection Type:** Threaded internal both ends Spline Pressure Angle In Deg: 14.5 both ends Spline Length: 0.232 inches and 0.255 inches both ends Spline Type: Involute both ends Setscrew: Not included both ends **Casing Material:**

Steel

NSN 1680-00-528-1729

Flexible Shaft Assembly - Page 2 of 2



Wrenching Facility Type: Hexagon both ends **Cross Section Size And Location:** 0.406 inches diameter both ends **Casing Length Between Ferrules:** 8.750 inches **Casing Outside Diameter:** 0.445 inches Swivel End: Not provided both ends **Lubrication Fitting:** Not provided both ends **Corelength:** 9.688 inches **Core Rotation Direction:** Clockwise or counterclockwise **Core Removability:** Removable **Fsc Application Data:** Flap, cowl installation, aircraft Shelf Life: N/a Unit Of Measure: ---Demilitarization: Yes - demil/mli

Fiig:

Т246-е