

NSN 1680-00-536-7797 Flexible Shaft Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/1680-00-536-7797 **Thread Class:** 2a both ends **Thread Direction:** Right-hand both ends Thread Length: 0.250 inches both ends **Spline Major Diameter:** 0.414 inches both ends **Overall Length:** 8.350 inches **Spline Quantity:** 10 both ends **Spline Minor Diameter:** 0.406 inches both ends Tip Length: 0.625 inches both ends **Shank Outside Diameter:** 0.502 inches both ends Pitch Diameter: 0.250 inches both ends **Core Material:** Steel **Screw Thread Series Designator:** Uns both ends **Core Diameter:** 0.250 inches **Thread Location:**

Internal both ends

End Type:

Round, internal splined both ends

Width Across Flats:

0.750 inches both ends

End Connection Type:

Threaded internal both ends

Spline Pressure Angle In Deg:

30.0 both ends

Spline Length:

0.4687 inches both ends

Spline Type:

Involute both ends

Setscrew:

Not included both ends

NSN 1680-00-536-7797Flexible Shaft Assembly - Page 2 of 2



Casing Material:
Steel
Wrenching Facility Type:
Hexagon both ends
Cross Section Size And Location:
0.414 inches diameter both ends
Torsional Deflection Rating:
5 degrees ft-lb in winding, 7 degrees ft-lb in unwinding
Casing Length Between Ferrules:
7.000 inches
Casing Outside Diameter:
0.455 inches
Swivel End:
Provided both ends
Enddiameter:
0.875 inches both ends
Lubrication Fitting:
Not provided both ends
Corelength:
8.350 inches
Core Rotation Direction:
Clockwise or counterclockwise
Core Removability:
Nonremovable
Minimum Operating Radius:
10.000 inches
Fsc Application Data:
Miscellaneous aircraft accessories and components
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T246-e