

View Online at <https://aerobasegroup.com/nsn/1680-00-540-1373>

Thread Class:

3 both ends

Thread Direction:

Right-hand both ends

Overall Length:

42.000 inches

Thread Depth:

0.562 inches both ends

Tip Length:

1.000 inches both ends

Shank Outside Diameter:

1.031 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Unef both ends

Core Diameter:

0.375 inches

Thread Location:

Internal both ends

End Type:

Square male both ends

Width Across Flats:

1.313 inches both ends

End Connection Type:

Threaded internal both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Hexagon both ends

Cross Section Size And Location:

0.300 inches diameter and 0.305 inches diameter both ends

Torsional Deflection Rating:

6.0 degrees ft-lb in. Torsional deflection rating in winding direction and 13.0 degrees ft-lb in. Torsional deflection rating in unwinding direction

Casing Length Between Ferrules:

40.000 inches

Casing Outside Diameter:

0.656 inches

Swivel End:

Not provided both ends

Enddiameter:

1.313 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

42.000 inches

Core Rotation Direction:

Counterclockwise

Core Removability:

Removable

Minimum Operating Radius:

6.000 inches

Fsc Application Data:

Shaft installation, ammunition booster

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T246-e