

View Online at <https://aerobasegroup.com/nsn/1680-00-540-1930>

**Thread Class:**

3b or 2 both ends

**Thread Direction:**

Right-hand both ends

**Spline Major Diameter:**

0.303 inches both ends

**Overall Length:**

12.8474 inches

**Spline Quantity:**

12 both ends

**Spline Minor Diameter:**

0.217 inches both ends

**Thread Depth:**

0.310 inches both ends

**Tip Length:**

0.4687 inches both ends

**Shank Outside Diameter:**

0.4375 inches both ends

**Pitch Diameter:**

0.250 inches both ends

**Core Material:**

Steel

**Screw Thread Series Designator:**

Uns both ends

**Core Diameter:**

0.276 inches

**Thread Location:**

Internal both ends

**End Type:**

Round, internal splined both ends

**Width Across Flats:**

0.750 inches both ends

**End Connection Type:**

Threaded internal both ends

**Spline Pressure Angle In Deg:**

14.5 both ends

**Spline Length:**

0.275 inches both ends

**Spline Type:**

Involute both ends

**Setscrew:**

Not included both ends

**Casing Material:**

Steel

**Wrenching Facility Type:**

Hexagon both ends

**Cross Section Size And Location:**

0.409 inches diameter both ends

**Casing Surface Treatment:**

Cadmium plated

**Casing Length Between Ferrules:**

11.910 inches

**Casing Outside Diameter:**

0.375 inches

**Swivel End:**

Not provided both ends

**Enddiameter:**

0.875 inches both ends

**Lubrication Fitting:**

Not provided both ends

**Corelength:**

12.8474 inches

**Core Rotation Direction:**

Clockwise or counterclockwise

**Core Removability:**

Nonremovable

**Minimum Operating Radius:**

2.500 inches

**Fsc Application Data:**

Shaft installation, trailing edge flap, aircraft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T246-e