

NSN 1680-00-580-3591 Flexible Shaft Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/1680-00-580-3591 **Thread Class:** 2a both ends **Thread Direction:** Right-hand both ends Thread Length: 0.500 inches both ends **Spline Major Diameter:** 0.303 inches both ends **Overall Length:** 18.188 inches **Spline Quantity:** 12 both ends **Spline Minor Diameter:** 0.242 inches both ends Tip Length: 0.469 inches both ends **Shank Outside Diameter:** 0.563 inches both ends **Shoulder Outside Diameter:** 0.500 inches both ends **Core Material:** Steel **Screw Thread Series Designator:** Uns both ends **Core Diameter:** 0.212 inches

Thread Location:

Internal both ends

End Type:

Round, internal splined both ends

Width Across Flats:

0.750 inches both ends

End Connection Type:

Threaded internal both ends

Spline Pressure Angle In Deg:

14.5 both ends

Spline Length:

0.250 inches both ends

Spline Type:

Involute both ends

Setscrew:

Not included both ends

NSN 1680-00-580-3591

Flexible Shaft Assembly - Page 2 of 2



Casing Material:
Steel
Wrenching Facility Type:
Hexagon both ends
Cross Section Size And Location:
0.406 inches diameter both ends
Torsional Deflection Rating:
2.5 degrees ft-lb in. Winging and unwinding torsional deflection rating
Casing Surface Treatment:
Zinc
Casing Length Between Ferrules:
17.250 inches
Casing Outside Diameter:
0.475 inches
Casing Protective Device Type:
Rubber cover
Swivel End:
Provided both ends
Enddiameter:
0.750 inches both ends
Lubrication Fitting:
Not provided both ends
Corelength:
18.188 inches
Core Rotation Direction:
Clockwise
Core Removability:
Nonremovable
Minimum Operating Radius:
3.000 inches
Fsc Application Data:
Pedal, control, aircraft
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
T246-e