## NSN 1680-00-594-4455

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1680-00-594-4455

Overall Length:
3.973 inches
Flange Thickness:
0.063 inches both ends
Tip Length:
0.625 inches both ends
Shank Outside Diameter:
0.500 inches both ends
Core Material:
Steel
Core Diameter:
0.250 inches
End Type:
Hexagon male both ends
End Connection Type:
Union ferrule both ends
Setscrew:
Not included both ends
Casing Material:
Steel
Cross Section Size And Location:
0.225 inches across flats both ends
Torsional Deflection Rating:
5.0 degrees per in. Ft-lb winding and 7.0 degrees per in. Ft-lb unwinding direction
Casing Length Between Ferrules:
3.469 inches
Casing Outside Diameter:
0.445 inches
Swivel End:
Not provided both ends
Enddiameter:
0.562 inches both ends
Lubrication Fitting:
Not provided both ends
Corelength:
3.973 inches
Core Rotation Direction:
Clockwise or counterclockwise
Core Removability:
Nonremovable
Minimum Operating Radius:

10.000 inches

## NSN 1680-00-594-4455

Flexible Shaft Assembly - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

T246-e