

View Online at <https://aerobasegroup.com/nsn/1680-00-618-2142>

**Thread Class:**

2b both ends

**Thread Direction:**

Right-hand both ends

**Overall Length:**

21.374 inches

**Thread Depth:**

0.328 inches both ends

**Tip Length:**

0.879 inches both ends

**Shank Outside Diameter:**

0.812 inches both ends

**Core Material:**

Steel

**Screw Thread Series Designator:**

Unef both ends

**Core Diameter:**

0.375 inches

**Thread Location:**

Internal both ends

**End Type:**

Round, internal splined both ends

**Width Across Flats:**

0.875 inches both ends

**End Connection Type:**

Union ferrule both ends

**Setscrew:**

Not included both ends

**Casing Material:**

Steel

**Wrenching Facility Type:**

Hexagon both ends

**Cross Section Size And Location:**

0.469 inches diameter both ends

**Torsional Deflection Rating:**

12 degrees ft-lb in. Torsional deflection rating winding, 16 degrees unwinding

**Casing Length Between Ferrules:**

19.612 inches

**Casing Outside Diameter:**

0.790 inches

**Casing Protective Device Type:**

Rubber cover

**Swivel End:**

Not provided both ends

**Enddiameter:**

0.531 inches both ends

**Lubrication Fitting:**

Not provided both ends

**Corelength:**

21.374 inches

**Core Rotation Direction:**

Clockwise or counterclockwise

**Core Removability:**

Nonremovable

**Minimum Operating Radius:**

18.000 inches

**Fsc Application Data:**

Miscellaneous aircraft accessories and components

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T246-e