

View Online at <https://aerobasegroup.com/nsn/1680-00-700-2081>

**Bore Diameter:**

Between 1.814 inches and 1.815 inches

**Bore Length:**

1.939 inches

**Special Features:**

Between casehardening indicator, not casehardened; angle in degrees is 90.0; accessory components and quantity is bushing, 4; bearings not included; counterbore feature not included; fulcrum bore provided; fulcrum shaft not included; fulcrum split hub not provided; center to center distance between fulcrum and aa arm end hole is 3.703 inches ; aa arm end radius is 0.750 inches ; aa arm end hole diameter is 0.312 inches and 0.313 inches ; center to center distance between fulcrum and bb arm end hole is 4.000 in ; bb arm radius is 0.750 in ; aa arm end thickness is 1.344 in ; bb arm thickness is 1.375 in ; aa arm slot depth is 1.750 in ; bb arm end hole diameter is 0.312 in min. And 0.313 in max; bb arm end thickness is 1.344 in ; bb arm slot depth is 1.750 in ; aa arm slot width is 0.903 in min and 0.913 in max; bb arm horizontal slot width is 0.903 in min and 0.913 in max

**Material:**

Aluminum alloy

**Surface Treatment:**

Anodize

**Style Designator:**

Clevis ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A523z0