# NSN 1680-00-765-9849

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1680-00-765-9849

Thread Class:	
3b both ends	
Thread Direction:	
Right-hand both ends	
Overall Length:	
102.250 inches	
Wrenching Facility Outside Diameter:	
0.750 inches both ends	
Thread Depth:	
0.250 inches both ends	
Core Material:	
Steel	
Screw Thread Series Designator:	
Uns both ends	
Core Diameter:	
0.250 inches	
Thread Location:	
Internal both ends	
End Connection Type:	
Threaded internal both ends	
Casing Material:	
Steel	
Wrenching Facility Type:	
Knurled surface both ends	
Torsional Deflection Rating:	
6.4 degrees ft-lb in.	
Casing Surface Treatment:	
Cadmium plated	
Casing Length Between Ferrules:	
101.250 inches	
Casing Outside Diameter:	
0.445 inches	
Swivel End:	
Not provided both ends	
Enddiameter:	
0.750 inches both ends	
Lubrication Fitting:	
Not provided both ends	
Corelength:	
0.750 inches	
Core Removability:	
Nonremovable	

# NSN 1680-00-765-9849

Flexible Shaft Assembly - Page 2 of 2



Minimum Operating Radius:

10.000 inches

#### **Special Features:**

Prepacked at manufacturer with grease type mil-g-7421

## **Fsc Application Data:**

H box, leading edge flap, aircaraft

### Shelf Life:

N/a

### Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

#### Fiig:

T246-e