

NSN 1680-00-765-9849 Flexible Shaft Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/1680-00-765-9849 **Thread Class:** 3b both ends **Thread Direction:** Right-hand both ends **Overall Length:** 102.250 inches **Wrenching Facility Outside Diameter:** 0.750 inches both ends **Thread Depth:** 0.250 inches both ends **Core Material:** Steel **Screw Thread Series Designator:** Uns both ends **Core Diameter:** 0.250 inches **Thread Location:** Internal both ends **End Connection Type:** Threaded internal both ends **Casing Material:** Steel

**Wrenching Facility Type:** 

Knurled surface both ends

**Torsional Deflection Rating:** 

6.4 degrees ft-lb in.

**Casing Surface Treatment:** 

Cadmium plated

**Casing Length Between Ferrules:** 

101.250 inches

**Casing Outside Diameter:** 

0.445 inches

Swivel End:

Not provided both ends

**Enddiameter:** 

0.750 inches both ends

**Lubrication Fitting:** 

Not provided both ends

Corelength:

0.750 inches

Core Removability:

Nonremovable

# NSN 1680-00-765-9849

Flexible Shaft Assembly - Page 2 of 2



# **Minimum Operating Radius:**

10.000 inches

### **Special Features:**

Prepacked at manufacturer with grease type mil-g-7421

# **Fsc Application Data:**

H box, leading edge flap, aircaraft

Shelf Life:

N/a

**Unit Of Measure:** 

--

### Demilitarization:

Yes - demil/mli

Fiig:

T246-e