## NSN 1680-00-808-4230

Flexible Shaft Assembly - Page 1 of 2



, ,
View Online at https://aerobasegroup.com/nsn/1680-00-808-4230
Thread Class:
2b both ends
Thread Direction:
Right-hand both ends
Overall Length:
95.163 inches
Thread Depth:
0.220 inches both ends
Core Material:
Steel
Screw Thread Series Designator:
Uns both ends
Core Diameter:
0.276 inches
Thread Location:
Internal both ends
Width Across Flats:
0.870 inches both ends
End Connection Type:
Threaded internal both ends
Casing Material:
Steel
Wrenching Facility Type:
Hexagon both ends
Torsional Deflection Rating:
30 degrees ft-lb in.
Casing Surface Treatment:
Zinc coated
Casing Length Between Ferrules:
94.120 inches
Casing Outside Diameter:
0.530 inches
Swivel End:
Not provided both ends
Enddiameter:
0.620 inches both ends

Corelength:

**Lubrication Fitting:**Not provided both ends

95.163 inches

**Core Rotation Direction:** 

Clockwise or counterclockwise

## NSN 1680-00-808-4230

Flexible Shaft Assembly - Page 2 of 2



Core	Remov	ability:

Nonremovable

**Minimum Operating Radius:** 

12.000 inches

**Fsc Application Data:** 

Actuators, mechanical, trim tab

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

T246-e