

View Online at <https://aerobasegroup.com/nsn/1680-00-849-2411>

Thread Class:

2b both ends

Thread Direction:

Right-hand both ends

Overall Length:

31.360 inches

Thread Depth:

0.870 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Uns both ends

Core Surface Treatment:

Lubricant, impregnated

Core Diameter:

0.275 inches

Thread Location:

Internal both ends

End Connection Type:

Threaded internal both ends

Casing Material:

Steel, corrosion resisting

Wrenching Facility Type:

Knurled surface both ends

Torsional Deflection Rating:

0.9 degrees ft-lb in. Winding and 1.1 degrees ft-lb in. Unwinding torsional deflection

Casing Length Between Ferrules:

28.800 inches

Casing Outside Diameter:

0.440 inches

Casing Protective Device Type:

Coiled spring protector

Swivel End:

Not provided both ends

Enddiameter:

0.750 inches both ends

Corelength:

31.360 inches

Core Rotation Direction:

Clockwise or counterclockwise

Core Removability:

Nonremovable

Minimum Operating Radius:

4.000 inches

Fsc Application Data:

Actuator, electro-mechanical, rotary, aircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T246-e