NSN 1680-00-879-1442

Ballast Weight - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/1680-00-879-1442

General Description:

Lead-antimony ams7720, surface finish, red enamel federal standard 595 no. 11136, white letters no. 17875, dim., 10.800 in. Nom lg, 4.300 in. Min, 4.350 in. Maximum od, 1.400 in. Min, 1.450 in. Maxid, 1.600 in. Min, 1.650 in. Maximum id counterbored right end 1.200 in. Deep, four holes 0.505 in. Min, 0.525 in. Maxdia drilled through od, two holes located 1.500 in. From right end and 1.400 in. Each side of horizontal centerline, twoholes 5.500 in. From right end and 1.400 in. From each side of horizontalcenterline, holes counterbored to 1.250in. Min, 1.255 in. Maximum diameter by 0.900 in.Deep, cylinder cut perpendicular to holes w/0.062 to 0.250 in. Maximum gap, weight 50.000 lbs used on all uh1 tailskids to move center of gravity to compensate for forward loading, assembly consists of 18 components, twoweight halves, 8 washers an 960-816l, four bolts an 8-27a and four nuts ms21044n,

Shelf Life:	
-------------	--

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli