NSN 1680-00-924-5301

Overall Length: 21.002 inches

Flange Thickness: 0.904 inches both ends

0.4062 inches both ends

Shank Outside Diameter:

Tip Length:

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1680-00-924-5301

Shank Outside Diameter:
0.406 inches both ends
Core Material:
Nickel copper alloy
Core Diameter:
0.187 inches
End Type:
Square male both ends
Width Across Flats:
0.750 inches both ends
End Connection Type:
Plain ferrule both ends
Setscrew:
Not included both ends
Casing Material:
Phosphor bronze
Wrenching Facility Type:
Hexagon both ends
Cross Section Size And Location:
0.154 inches across flats second end
Casing Length Between Ferrules:
19.253 inches
Casing Outside Diameter:
0.317 inches
Casing Protective Device Type:
Coiled spring protector
Swivel End:
Not provided both ends
Enddiameter:
0.563 inches both ends
Lubrication Fitting:
Not provided both ends
Corelength:
20.190 inches
Core Rotation Direction:
Clockwise

NSN 1680-00-924-5301

Flexible Shaft Assembly - Page 2 of 2



Core Removability:
Nonremovable
Minimum Operating Radius:
6.000 inches
Fsc Application Data:
Windshield wiper installation, aircraft
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T246-e