

View Online at <https://aerobasegroup.com/nsn/1680-00-975-0196>

General Description:

Aluminum alloy qq-a-250/4 comp 2024 cond o, tile, ceramic, high strength commercial grade, cloth, nylon, ballistic mil-c-12369, block, support, aluminum alloy qq-a-225/9 comp 7075-t6 or qq-a-200/11 comp 7075-t6, dim., 27.500 in. Nom lg, 17.500 in. Nom w, 0.735 in. Maximum o/a thick, 0.485 in. Nom tile thickness, 0.250 in. Nom aluminum alloy thickness, block, support, 3.000 in. Nom lg, 2.000 in. Nom w, 0.500 in. Nom thick four holes 0.325 in. Nom diameter drilled through block at each corner 0.500 in. From top and 0.560 in. From each side, two threaded holes, 0.250-20 unc 3b thread size, located 0.500 in. From top and bottom and 1.500 in. From side, blocks secured to left and right sides of panel 8.996 in. From bottom, two 8.000 in. Lg sections 1.250 in. W bent at right angle to plate on left and right sides 1.870 in. From bottom and drilled w/five 0.301 in. Nom diameter holes on 7.000 in. Bsc 0.750 in. From plate, aluminum and tile bonded w/proseal 890b1/2, composite armor weight 10.5 psf max, used as panel back co-pilots armor

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli