

View Online at <https://aerobasegroup.com/nsn/1680-00-975-0199>

General Description:

Aluminum alloy qq-a-250/4 comp 2024 cond o, tile, ceramic, high strength commercial grade, cloth, nylon, ballistic mil-c-12369, block, aluminum alloy qq-a-225/9 comp 7075-t6 or qq-a-200/11 comp 7075-t6, dim., 17.500 in. Nom lg, 16.580 in. Nom w, 0.735 in. Maximum thick, 0.438 in. Nom tile thickness, 0.250 in. Nom aluminum alloy thickness, top edge and both sides bent at 83.0 degrees angle by 1.250 in. Nom wide w/8 holes 0.301 in. Diameter equally spaced on 14.000 in. Bsc, bottom edge bent at 60.0 degrees angle by 1.120 in. Wide, block, support 3.000 in. Nom lg, 2.550 in. Nom w, 0.500 in. Nom thick, four holes 0.325 in. Nom diadrilled through block at each corner 1.000 in. From top and 0.560 in. From each side w/1.000 in. Center to center distance, two threaded holes w/0.250-20 unc 3b threads located 1.000 in. From top, 0.550 in. From bottom and 1.500 in. From side, block secured at top left and right sides of panel w/inside holes at 3.700 in. Bsc from edges, aluminum and tile bonded w/proseal 890b1/2, composite armor weight 10.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli