## NSN 1680-00-975-7890

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1680-00-975-7890
Thread Class:
2b both ends
Thread Direction:
Right-hand both ends
Overall Length:
22.140 inches
Thread Depth:
0.250 inches both ends
Core Material:
Steel
Screw Thread Series Designator:
Uns both ends
Core Diameter:
0.250 inches
Thread Location:
Internal both ends
Width Across Flats:
0.750 inches both ends
End Connection Type:
Union ferrule both ends
Casing Material:
Steel, corrosion resisting
Wrenching Facility Type:
Hexagon both ends
Casing Surface Treatment:
Passivated
Casing Length Between Ferrules:
20.668 inches
Casing Outside Diameter:
0.445 inches
Swivel End:
Not provided both ends
Enddiameter

**Enddiameter:** 

0.875 inches both ends

**Lubrication Fitting:** 

Not provided both ends

Corelength:

22.140 inches

**Core Rotation Direction:** 

Clockwise or counterclockwise

Core Removability:

Nonremovable

## NSN 1680-00-975-7890

Flexible Shaft Assembly - Page 2 of 2



Minimum Operating Radius	١	A	i	n	iı	m	u	m	1	0	p	е	ra	ıti	n	q	ı	₹	a	d	į	u	S	;	:
--------------------------	---	---	---	---	----	---	---	---	---	---	---	---	----	-----	---	---	---	---	---	---	---	---	---	---	---

10.000 inches

**Fsc Application Data:** 

Miscellaneous aircraft accessories and components

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

T246-e