

View Online at <https://aerobasegroup.com/nsn/1680-01-072-1731>

General Description:

Aluminum alloy, qq-a-225/6 comp 2024 temper t4; anodized, mil-a-8625 type 1; 5.430 in. Min, 5.440 in. Maximum od external flange; 4.245 in. Min, 4.255 in. Maximum id external flange, 0.834 in. Min, 0.854 in. Maximum lg external flange; 1.140 in. Min, 1.170 in. Maximum o/a lg; 4.220 in. Min, 4.250 in. Maximum od internal flange, 4.072 in. Min, 4.077 in. Maximum id internal flange; 4 holes 0.127 in. Min, 0.137 in. Maximum diameter through internal flange outer periphery, 0.130 in. Min, 0.180 in. Maximum distance from 1st end to hole center; 2 thd holes through one wall of external flange face located on 2.500 in. Nom bolt circle dia, no. 6-32 unc series cl 2b thd; 1 hole 0.275 in. Min, 0.285 in. Maximum diameter through external flange face located on 2.250 in. Nom bolt circle; 1 hole 0.150 in. Min, 0.160 in. Maximum diameter through bottom wall of external flange on 2.250 in. Nom bolt circle dia, hole c0untersunk 95 min, 1.05 in. Maximum degrees to 0.270 in min, 0.285 in. Maximum dia

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli