

View Online at <https://aerobasegroup.com/nsn/1680-01-526-6613>

Terminal Type:

Connector

Reliability Indicator:

Established

Tempurature Rating:

-65.0 degrees fahrenheit and 165.0 degrees fahrenheit

Current Type:

Dc

Body Length:

7.750 inches

Body Width:

1.950 inches

Body Height:

3.380 inches

Operating Speed At Rated Capacity In Rpm:

79.0

End Application:

C17

Shaft Rotation Direction:

Clockwise and counterclockwise

Drive Type:

Gear

Duty Cycle:

Intermittent

Current Rating In Amps:

3.0

Rotation In Deg:

213.5

Output Drive Torque Rating:

50.0 inch-pounds

Limit Switch Control:

Included

Manual Override:

Not included

Angular Shaft Rotation:

Limited

Intermittent Operation Duty Cycle:

9.0 seconds on and 30.0 seconds off

Mounting Facility:

Mounting flanges

Product Name:

Apu door actuator

Voltage In Volts:

28.0

Special Test Features:

Fungus method 508.1 procedure i, altitude method 500.1 procedure i, shockmethod 516.2 procedure i, load method 513.2 procedure i

Test Data Document:

00268-mil-std-801 standard (includes industry or association standards, individual manufactureer standards, etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A30500