NSN 1720-00-883-9038



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/1720-00-883-9038 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.234 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 180.0 degrees fahrenheit single response **Outside Diameter:** 0.703 inches **Minimum Inside Bending Radius:** 3.250 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 16000.0 pounds per square inch **Layer Composition And Location:** 1st layer spirally wrapped corrosion resistant steel fabric and 2nd layer spirally wrapped corrosion resistant steel fabric and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 4000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 8000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 11.000 inches

N/a

Unf 1st end Shelf Life:

Unit Of Measure:

Thread Series Designator:

--

NSN 1720-00-883-9038

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0