NSN 1730-00-901-3024

Vehicular Mounting Aircraft Lavatory Servicing Tank-pumping Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/1730-00-901-3024

Special Features:

Operating temperatures - minus 20deg f to 160 degrees f; voltage - 110v ac, 12v dc; prime mover type - model 1600/or equilivent, international harveste r chasis; waste pump and motor operates at 1750 rpm; rinse pump and motor operates at 3350 rpm; 6 wheels with tire tread for mud and snow; tanks 3; compartments 3; type of tanks - waste and detergent; method of purification - water; method of filling - attached hose; purging method - fill and flush

Functional Description:

Provides a waste tank, fresh water tank, and detergent tank for flight line servicing of the c-141 aircraft

Reference Data And Literature:

T.O. 35d3-17-3-1

General Description:

Pump data, rotary type, elec motor driven, dc, 12 v; tank data, two individual tanks, 300 gal fresh water capacity, 400 gal waste capacity, 0 == : D: 00 (:) ١t

Shelf Life:
A/s32a-8
Type/model Designation:
tank
international harvester corp., model no. 1600, type 4x2; o/a dim., 241.8 in. Lg, 90.0 in. W, 102.5 in. H; special features, 30 gal, deterger
w/heater; hose data, 25 ft lg fresh water hose, 0.75 in. Dia, 20 ft lg waste hose, 2.0 in. Dia; data regarding the vehicle on which mtd,

Demilitarization:

Unit Of Measure:

No

N/a

Fiig:

A23900