

View Online at <https://aerobasegroup.com/nsn/1730-00-901-3024>

Special Features:

Operating temperatures - minus 20deg f to 160 degrees f; voltage - 110v ac, 12v dc; prime mover type - model 1600/or equivalent, international harvester chassis; waste pump and motor operates at 1750 rpm; rinse pump and motor operates at 3350 rpm; 6 wheels with tire tread for mud and snow; tanks 3; compartments 3; type of tanks - waste and detergent; method of purification - water; method of filling - attached hose; purging method - fill and flush

Functional Description:

Provides a waste tank, fresh water tank, and detergent tank for flight line servicing of the c-141 aircraft

Reference Data And Literature:

T.O. 35d3-17-3-1

General Description:

Pump data, rotary type, elec motor driven, dc, 12 v; tank data, two individual tanks, 300 gal fresh water capacity, 400 gal waste capacity, w/heater; hose data, 25 ft lg fresh water hose, 0.75 in. Dia, 20 ft lg waste hose, 2.0 in. Dia; data regarding the vehicle on which mtd, international harvester corp., model no. 1600, type 4x2; o/a dim., 241.8 in. Lg, 90.0 in. W, 102.5 in. H; special features, 30 gal, detergent tank

Type/model Designation:

A/s32a-8

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A23900