

View Online at <https://aerobasegroup.com/nsn/1730-01-370-4268>

Locking Device:

Included

Adjustability:

Adjustable

Floor Material:

Steel

Adjustment Method:

Hydraulic

Rolling Element Type And Quantity:

4 wheel

Working Level Dimension:

36 ft elevated height

Working Platform Quantity:

1

Ladder:

Not included

Platform Safety Guard:

Included

Safety Guard Type:

Adjustable

Maximumlength:

201.000 inches

Maximumwidth:

157.000 inches

Maximumheight:

122.000 inches

Rated Load Capacity:

2000.0 pounds

Product Name:

Maintenance platform, split deck, diesel

Special Features:

Height is with platform elevated; width is with outrigger extended; width with outrigger retracted 13.1 ft; height to platform (lowered) 6.7 ft; platform width 8 ft; platform length 15 ft 5 inches; platform extension 8 ft; weight 14, 500 lbs; gradeability type 25%; self propelled speed (lowered) 3 mph, (elevated) 0.3 mph; maximum towing speed 15 mph; outside turning circle 40.25 ft; maximum side wind (elevated) 15 mph; preferred fuel diesel no. 2, alternative fuel jp4, jp5, jp8; tires 12-16.5 10 ply rated highway type; fuel capaci type 18 gal; includes davit; davit load capaci type 250 lbs at outermost position, 500 lbs at mid position

Functional Description:

Diesel powered platform, self propelled, hydraulically operated; consists of a box tube chassis frame supporting a pantographing steel scissors lift mechanism that extends upward, raising a work surface platform; the platform may be extended forward to any height; may be driven or towed, including being driven while elevated; designed to be used in class i div 2 group d hazardous environments

Reference Data And Literature:

T.O. 35a4-2-67-1

Relationship To Similar Equipment:

Similar to nsn 1730-01-118-5451 plus engineering change proposals

Shelf Life:

Demilitarization:

No

Fig:

T361-j