

View Online at <https://aerobasegroup.com/nsn/2010-00-068-4025>

Inside Diameter:

Between 1.750 inches and 4.500 inches

Major Diameter:

4.500 inches

Thread Length:

3.875 inches

Width:

Between 1.375 inches and 1.437 inches

Overall Length:

31.167 feet

Outside Diameter:

6.500 inches

Taper Length:

1.333 feet

Taper Major Diameter:

6.500 inches

Keyway Width:

Between 1.375 inches and 1.437 inches

Keyway Depth:

0.505 inches

Depth:

0.505 inches

Keyway Quantity:

2 and 3

Surface Finish:

Smooth machined

Intermediate Bearing Sleeve Outside Diameter:

7.500 inches

Intermediate Bearing Sleeve Length:

1.792 feet

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Hollow

Thread Quantity:

4 per inch

Usage Location:

Center

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Taper Length:

0.448 feet

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

7.500 inches

Forward Bearing Sleeve Length:

36.000 feet

After Bearing Sleeve Outside Diameter:

7.500 inches

After Bearing Sleeve Length:

30.000 feet

Covering Location:

Surfaces between bearing sleeves covered

Forward End Taper Major Diameter:

7.250 inches

Taper:

1.000 per foot in inches

Forward End Taper:

0.125 per foot in inches

Material:

Steel, mil, mil-s-890 cl an, forged

Material:

Steel, mil, mil-s-890 cl an, forged

Quantity:

2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T08000