

View Online at <https://aerobasegroup.com/nsn/2010-00-068-4025>

**Inside Diameter:**

Between 1.750 inches and 4.500 inches

**Major Diameter:**

4.500 inches

**Thread Length:**

3.875 inches

**Width:**

Between 1.375 inches and 1.437 inches

**Overall Length:**

31.167 feet

**Outside Diameter:**

6.500 inches

**Taper Length:**

1.333 feet

**Taper Major Diameter:**

6.500 inches

**Keyway Width:**

Between 1.375 inches and 1.437 inches

**Keyway Depth:**

0.505 inches

**Depth:**

0.505 inches

**Keyway Quantity:**

2 and 3

**Surface Finish:**

Smooth machined

**Intermediate Bearing Sleeve Outside Diameter:**

7.500 inches

**Intermediate Bearing Sleeve Length:**

1.792 feet

**Unit Type:**

Propeller shaft section

**Protective Covering Type:**

Rubber

**Construction:**

Hollow

**Thread Quantity:**

4 per inch

**Usage Location:**

Center

**Forward End Design:**

Tapered

**Forward End Keyway:**

Provided

**After End Keyway:**

Provided

**Forward End Taper Length:**

0.448 feet

**Threaded Forward End:**

Not included

**After End Design:**

Tapered

**Threaded After End:**

Included

**Forward Bearing Sleeve Outside Diameter:**

7.500 inches

**Forward Bearing Sleeve Length:**

36.000 feet

**After Bearing Sleeve Outside Diameter:**

7.500 inches

**After Bearing Sleeve Length:**

30.000 feet

**Covering Location:**

Surfaces between bearing sleeves covered

**Forward End Taper Major Diameter:**

7.250 inches

**Taper:**

1.000 per foot in inches

**Forward End Taper:**

0.125 per foot in inches

**Material:**

Steel, mil, mil-s-890 cl an, forged

**Material:**

Steel, mil, mil-s-890 cl an, forged

**Quantity:**

2

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T08000