

View Online at <https://aerobasegroup.com/nsn/2010-00-068-7520>

Major Diameter:

7.500 inches

Thread Length:

7.000 inches

Width:

2.498 inches

Overall Length:

34.593 feet

Outside Diameter:

11.625 inches

Taper Length:

1.667 feet

Taper Major Diameter:

11.625 inches

Keyway Width:

1.375 inches and 1.437 inches

Keyway Depth:

0.547 inches and 0.551 inches

Depth:

0.896 inches

Keyway Quantity:

3 and 1

Surface Finish:

Smooth machined

Usage Design:

T-ags 26, 27

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Solid

Thread Quantity:

4 per inch

Usage Location:

Center

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Coupling Design:

Detachable

Forward End Coupling Type:

Flange

Forward End Coupling Outside Diameter:

12.000 inches

Forward End Coupling Length:

0.781 feet

Forward End Coupling Thickness:

4.688 inches

Forward End Taper Length:

0.812 feet

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

13.063 inches

Forward Bearing Sleeve Length:

4.583 feet

After Bearing Sleeve Outside Diameter:

13.063 inches

After Bearing Sleeve Length:

4.917 feet

Covering Location:

Surface between bearing sleeves covered

Forward End Taper Major Diameter:

10.250 inches

Taper:

1.000 per foot in inches

Forward End Taper:

0.125 per foot in inches

Material:

Steel, abs, grade 2, forged

Material:

Steel, abs, grade 2, forged

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T08000