

View Online at <https://aerobasegroup.com/nsn/2010-00-127-4796>

Major Diameter:

1.750 inches

Thread Length:

2.813 inches

Width:

0.625 inches

Overall Length:

9.604 feet

Outside Diameter:

2.500 inches

Taper Length:

0.635 feet

Taper Major Diameter:

Between 2.440 inches and 2.441 inches

Keyway Width:

0.625 inches

Keyway Depth:

0.313 inches

Depth:

0.313 inches

Keyway Quantity:

1

Surface Finish:

Smooth machined

Furnished Items And Quantity:

Jam nut, 1, propeller nut, 1, cotter pin, 2

Unit Type:

Propeller shaft section

Construction:

Solid

Thread Quantity:

3 per inch

Usage Location:

Port/starboard

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Taper Length:

0.604 feet

Threaded Forward End:

Included

Forward End Major Diameter:

1.750 inches

Forward End Thread Quantity:

3 per inch

Forward End Thread Length:

1.688 inches

After End Design:

Tapered

Threaded After End:

Included

After Bearing Sleeve Outside Diameter:

Between 2.749 inches and 2.751 inches

After Bearing Sleeve Length:

1.167 feet

Forward End Taper Major Diameter:

Between 2.4395 inches and 2.4405 inches

Taper:

0.750 per foot in inches

Forward End Taper:

0.750 per foot in inches

Material:

Brass, astm b21-66a, 464

Material:

Brass, astm b21-66a, 464

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T08000