NSN 2010-00-248-6828

Ship Propulsion Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2010-00-248-6828

Inside Diameter:

Between 6.457 inches and 6.496 inches

Overall Length:

32.999 feet

Outside Diameter:

11.496 inches

End Application:

Onboard 282 ft wmec coast guard vessels

Surface Finish:

Smooth machined

Coupling Outside Diameter:

23.228 inches

Unit Type:

Stern tube shaft section

Protective Covering Type:

Rubber

Construction:

Hollow

Usage Location:

Port/starboard

Forward End Keyway:

Not provided

After End Keyway:

Not provided

Forward End Coupling Design:

Integral

Forward End Coupling Outside Diameter:

17.716 inches

Forward End Coupling Length:

0.180 feet

Forward End Coupling Thickness:

2.165 inches

Threaded Forward End:

Not included

After End Coupling Design:

Integral

Coupling Length:

0.262 feet

Coupling Thickness:

3.149 inches

Threaded After End:

Not included

NSN 2010-00-248-6828

Ship Propulsion Shaft - Page 2 of 2



Forward Bearing Sleeve Outside Diameter: Between 12.874 inches and 12.875 inches Forward Bearing Sleeve Length: 5.522 feet After Bearing Sleeve Outside Diameter: Between 13.749 inches and 13.750 inches After Bearing Sleeve Length: 7.953 feet **Covering Location:** Surfaces between bearing sleeves Material: Steel, mil-s-23284, class 3 Material: Steel, mil-s-23284, class 3 Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: T08000