

View Online at <https://aerobasegroup.com/nsn/2010-00-248-6829>

Inside Diameter:

Between 6.457 inches and 6.496 inches

Overall Length:

26.000 feet

Outside Diameter:

13.977 inches

End Application:

Onboard 282 ft wmec coast guard vessels

Surface Finish:

Smooth machined

Coupling Outside Diameter:

32.263 inches

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Hollow

Usage Location:

Port/starboard

Forward End Keyway:

Not provided

After End Keyway:

Not provided

Forward End Coupling Design:

Integral

Forward End Coupling Outside Diameter:

23.228 inches

Forward End Coupling Length:

0.262 feet

Forward End Coupling Thickness:

3.149 inches

Threaded Forward End:

Not included

After End Coupling Design:

Integral

Coupling Length:

0.295 feet

Coupling Thickness:

3.543 inches

Threaded After End:

Not included

Forward Bearing Sleeve Outside Diameter:

15.354 inches

Forward Bearing Sleeve Length:

0.984 feet

After Bearing Sleeve Outside Diameter:

15.728 inches

After Bearing Sleeve Length:

6.972 feet

Covering Location:

Surfaces between bearing sleeves

Material:

Steel, mil-s-23284, class 3

Material:

Steel, mil-s-23284, class 3

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T08000