

View Online at <https://aerobasegroup.com/nsn/2010-00-275-7701>

Inside Diameter:

4.000 inches

Major Diameter:

4.500 inches

Thread Length:

4.500 inches

Width:

1.324 inches

Overall Length:

48.145 feet

Outside Diameter:

7.000 inches

Taper Length:

1.312 feet

Taper Major Diameter:

7.000 inches

Depth:

0.515625 inches

Surface Finish:

Smooth machined

Furnished Items And Quantity:

Propeller nut, 1; propeller key, 2

Intermediate Bearing Sleeve Outside Diameter:

7.750 inches

Intermediate Bearing Sleeve Length:

3.547 feet

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Hollow

Thread Quantity:

4 per inch

Usage Location:

Port/starboard

Forward End Design:

Straight

Forward End Diameter:

7.000 inches

Forward End Keyway:

Not provided

After End Keyway:

Provided

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

7.750 inches

Forward Bearing Sleeve Length:

3.688 feet

After Bearing Sleeve Outside Diameter:

7.750 inches

After Bearing Sleeve Length:

4.688 feet

Covering Location:

Surfaces between bearing sleeve covered

Taper:

1.000 per foot in inches

Material:

Steel, mil-s-890, forged

Material:

Steel, mil-s-890, forged

Quantity:

2

Reference Number Differentiating Characteristics:

As differentiated by unit type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T08000