## NSN 2010-00-275-7701

Ship Propulsion Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2010-00-275-7701 **Inside Diameter:** 4.000 inches **Major Diameter:** 4.500 inches Thread Length: 4.500 inches Width: 1.324 inches **Overall Length:** 48.145 feet **Outside Diameter:** 7.000 inches **Taper Length:** 1.312 feet **Taper Major Diameter:** 7.000 inches Depth: 0.515625 inches **Surface Finish:** Smooth machined **Furnished Items And Quantity:** Propeller nut, 1; propeller key, 2 **Intermediate Bearing Sleeve Outside Diameter:** 7.750 inches **Intermediate Bearing Sleeve Length:** 3.547 feet **Unit Type:** Propeller shaft section **Protective Covering Type:** Rubber **Construction:** Hollow **Thread Quantity:** 4 per inch **Usage Location:** 

Port/starboard Forward End Design: Straight **Forward End Diameter:** 7.000 inches Forward End Keyway: Not provided

## **NSN 2010-00-275-7701**Ship Propulsion Shaft - Page 2 of 2



After End Keyway:
Provided
Threaded Forward End:
Not included
After End Design:
Tapered
Threaded After End:
Included
Forward Bearing Sleeve Outside Diameter:
7.750 inches
Forward Bearing Sleeve Length:
3.688 feet
After Bearing Sleeve Outside Diameter:
7.750 inches
After Bearing Sleeve Length:
4.688 feet
Covering Location:
Surfaces between bearing sleeve covered
Taper:
1.000 per foot in inches
Material:
Steel, mil-s-890, forged
Material:
Steel, mil-s-890, forged
Quantity:
2
Reference Number Differentiating Characteristics:
As differentiated by unit type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
T08000