

View Online at <https://aerobasegroup.com/nsn/2010-00-293-9803>

Inside Diameter:

10.000 inches

Major Diameter:

17.000 inches

Width:

4.500 inches

Overall Length:

40.912 feet

Outside Diameter:

25.500 inches

Taper Length:

4.125 feet

Taper Major Diameter:

25.500 inches

Keyway Width:

3.000 inches

Keyway Depth:

1.000 inches

Depth:

1.625 inches

Keyway Quantity:

4

Surface Finish:

Smooth machined

Furnished Items And Quantity:

1 propeller nut, 2 propeller keys, 4 coupling keys

Unit Type:

Propeller shaft section

Construction:

Hollow

Thread Quantity:

4 per inch

Usage Location:

Port/starboard

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Taper Length:

1.688 feet

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

27.750 inches

Forward Bearing Sleeve Length:

7.209 feet

After Bearing Sleeve Outside Diameter:

27.750 inches

After Bearing Sleeve Length:

10.917 feet

Forward End Taper Major Diameter:

23.000 inches

Taper:

1.000 per foot in inches

Forward End Taper:

0.125 per foot in inches

Material:

Steel, mil-s-890

Material:

Steel

Material Specification:

Mil-s-890 military specification single material response

Quantity:

2

Reference Number Differentiating Characteristics:

W/o protective covering

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T08000

Mil-std (military Standard):

Mil-s-890 spec.