

View Online at <https://aerobasegroup.com/nsn/2010-00-294-1659>

Inside Diameter:

10.500 inches

Major Diameter:

8.5000 inches

Thread Length:

9.0000 inches

Width:

Between 3.125 inches and 3.188 inches

Overall Length:

39.250 feet

Outside Diameter:

17.750 inches

Taper Length:

3.802 feet

Taper Major Diameter:

17.750 inches

Depth:

1.531 inches

Surface Finish:

Smooth machined

Furnished Items And Quantity:

Propeller nut, 1; propeller key, 2

Usage Design:

Suitable for dd931-933, 936-938, 940-944 vessels

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Hollow

Thread Quantity:

4 per inch

Usage Location:

Port/starboard

Forward End Keyway:

Not provided

After End Keyway:

Provided

Forward End Coupling Design:

Integral

Forward End Coupling Outside Diameter:

28.5000 inches

Forward End Coupling Length:

0.688 feet

Forward End Coupling Thickness:

3.500 inches

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

19.375 inches

Forward Bearing Sleeve Length:

4.667 feet

After Bearing Sleeve Outside Diameter:

19.375 inches

After Bearing Sleeve Length:

7.250 feet

Covering Location:

All exposed surfaces covered

Taper:

1.500 per foot in inches

Material:

Steel, mil-s-890, class an

Material:

Steel

Material Specification:

Mil-s-890, class an military specification single material response

Quantity:

2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T08000

Mil-std (military Standard):

Mil-s-890 spec.