NSN 2010-00-294-1663

Ship Propulsion Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2010-00-294-1663

Inside Diameter:
11.500 inches
Overall Length: 31.167 feet
Outside Diameter:
17.750 inches
Keyway Width:
Between 2.625 inches and 2.688 inches
Keyway Depth:
1.406 inches
Keyway Quantity:
4
Surface Finish:
Smooth machined
Coupling Outside Diameter:
28.500 inches
Furnished Items And Quantity:
Coupling key, 3; 2-11/16 in. W coupling key, 1
Usage Design:
Suitable for dd931-933, 936-938, 940-944 vessels
Unit Type:
Stern tube shaft section
Protective Covering Type:
Rubber
Construction:
Hollow
Usage Location:
Port/starboard
Forward End Design:
Tapered
Forward End Keyway:
Provided
After End Keyway:
Not provided
Forward End Taper Length:
1.333 feet
Threaded Forward End:
Not included
After End Coupling Design:
Integral
Coupling Thickness:
3.500 inches

NSN 2010-00-294-1663

Ship Propulsion Shaft - Page 2 of 2



Threaded After End: Not included Forward Bearing Sleeve Outside Diameter: 19.375 inches Forward Bearing Sleeve Length: 5.000 feet After Bearing Sleeve Outside Diameter: 19.375 inches After Bearing Sleeve Length: 4.667 feet **Covering Location:** All exposed surfaces covered Forward End Taper Major Diameter: 17.250 inches Material: Steel, mil-s-890, class an Material: Steel **Material Specification:** Mil-s-890, class an military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T08000 Mil-std (military Standard): Mil-s-890 spec.
