

View Online at <https://aerobasegroup.com/nsn/2010-00-300-9855>

**Major Diameter:**

Between 3.743 inches and 3.745 inches

**Thread Length:**

5.938 inches

**Width:**

Between 1.248 inches and 1.250 inches

**Overall Length:**

4.135 feet

**Outside Diameter:**

6.000 inches

**Taper Length:**

1.000 feet

**Taper Major Diameter:**

Between 5.001 inches and 5.002 inches

**Keyway Width:**

Between 0.998 inches and 1.000 inches

**Keyway Depth:**

Between 0.503 inches and 0.505 inches

**Depth:**

Between 0.442 inches and 0.455 inches

**Keyway Quantity:**

2

**Surface Finish:**

Smooth machined

**Unit Type:**

Propeller shaft section

**Construction:**

Solid

**Thread Quantity:**

5.938 per inch

**Forward End Design:**

Straight

**Forward End Diameter:**

Between 4.502 inches and 4.503 inches

**Forward End Keyway:**

Provided

**After End Keyway:**

Provided

**Threaded Forward End:**

Included

**Forward End Major Diameter:**

1.000 inches

**Forward End Thread Quantity:**

14 per inch

**Forward End Thread Length:**

1.500 inches

**After End Design:**

Tapered

**Threaded After End:**

Included

**Taper:**

0.750 per foot in inches

**Special Features:**

2nd keyway depth 0.252 in. Min by 0.255 in. Max; 2nd keyway width 0.499 in. Min by 0.500 in. Max

**Material:**

Steel, fed, qq-s-633a, composition b

**Material:**

Steel, fed, qq-s-633a, composition b

**Quantity:**

1

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T08000