

View Online at <https://aerobasegroup.com/nsn/2010-00-352-0397>

Inside Diameter:

10.500 inches

Major Diameter:

11.000 inches

Thread Length:

10.875 inches

Width:

2.750 inches

Overall Length:

53.583 feet

Outside Diameter:

16.250 inches

Taper Length:

3.240 feet

Taper Major Diameter:

16.250 inches

Depth:

0.875 inches

Surface Finish:

Smooth machined

Furnished Items And Quantity:

Propeller nut, 1; propeller key, 2

Usage Design:

For vessell class cl55-67, 76-94, 101-118; cvl22-30

Unit Type:

Propeller shaft section

Protective Covering Type:

Paint

Construction:

Hollow

Thread Quantity:

4 per inch

Usage Location:

Port/starboard or inboard/outboard

Forward End Keyway:

Not provided

After End Keyway:

Provided

Forward End Coupling Design:

Integral

Forward End Coupling Outside Diameter:

23.125 inches

Forward End Coupling Thickness:

3.250 inches

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

18.063 inches

Forward Bearing Sleeve Length:

8.417 feet

After Bearing Sleeve Outside Diameter:

18.063 inches

After Bearing Sleeve Length:

8.688 feet

Covering Location:

Surfaces between bearing sleeves covered

Taper:

1.000 per foot in inches

Material:

Steel, n, 49-s-2

Material:

Steel, n, 49-s-2

Quantity:

2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T08000