

View Online at <https://aerobasegroup.com/nsn/2010-00-352-0417>

Major Diameter:

4.000 inches

Thread Length:

4.500 inches

Width:

1.375 inches

Overall Length:

21.219 feet

Outside Diameter:

Between 5.500 inches and 6.090 inches

Taper Length:

1.208 feet

Taper Major Diameter:

6.090 inches

Depth:

0.4375 inches

Surface Finish:

Smooth machined

Furnished Items And Quantity:

Propeller nut, 1; propeller key, 1

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Solid

Thread Quantity:

4 per inch

Usage Location:

Port/starboard

Forward End Keyway:

Not provided

After End Keyway:

Provided

Forward End Coupling Design:

Integral

Forward End Coupling Outside Diameter:

14.375 inches

Forward End Coupling Thickness:

1.750 inches

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

6.750 inches

Forward Bearing Sleeve Length:

2.333 feet

After Bearing Sleeve Outside Diameter:

6.750 inches

After Bearing Sleeve Length:

2.917 feet

Covering Location:

Surfaces between bearing sleeve

Taper:

1.000 per foot in inches

Material:

Steel, mil-s-890

Material:

Steel

Material Specification:

Mil-s-890 military specification single material response

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T08000

Mil-std (military Standard):

Mil-s-890 spec.