

View Online at <https://aerobasegroup.com/nsn/2010-00-352-0429>

Major Diameter:

2.250 inches

Thread Length:

2.688 inches

Width:

0.750 inches

Overall Length:

8.583 feet

Outside Diameter:

4.000 inches

Taper Length:

0.750 feet

Taper Major Diameter:

4.000 inches

Keyway Width:

0.625 inches

Keyway Depth:

0.313 inches

Depth:

0.375 inches

Keyway Quantity:

2

Surface Finish:

Smooth machined

Furnished Items And Quantity:

Propeller nut, 1; propeller key, 1

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Solid

Thread Quantity:

4 per inch

Usage Location:

Port/starboard

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Taper Length:

0.750 feet

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

After Bearing Sleeve Outside Diameter:

4.750 inches

After Bearing Sleeve Length:

2.500 feet

Covering Location:

All exposed surfaces

Forward End Taper Major Diameter:

4.000 inches

Taper:

1.000 per foot in inches

Forward End Taper:

1.000 per foot in inches

Material:

Steel, mil-s-890

Material:

Steel

Material Specification:

Mil-s-890 military specification single material response

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T08000

Mil-std (military Standard):

Mil-s-890 spec.