NSN 2010-00-352-0480

Ship Propulsion Shaft - Page 1 of 2

Inside Diameter: 14.750 inches Overall Length:

Outside Diameter:

61.912 feet

23.062 inches

Keyway Width:



View Online at https://aerobasegroup.com/nsn/2010-00-352-0480

| 2.875 inches |
|-----------------------------------|
| Keyway Depth: |
| 1.375 inches |
| Keyway Quantity: |
| 4 |
| Surface Finish: |
| Smooth machined |
| Coupling Outside Diameter: |
| 38.000 inches |
| Usage Design: |
| For vessel class cvb41-43 |
| Unit Type: |
| Stern tube shaft section |
| Protective Covering Type: |
| Rubber |
| Construction: |
| Hollow |
| Usage Location: |
| Outboard or port/starboard |
| Forward End Design: |
| Tapered |
| Forward End Keyway: |
| Provided |
| After End Keyway: |
| Not provided |
| Forward End Taper Length: |
| 2.125 feet |
| Threaded Forward End: |
| Not included |
| After End Coupling Design: |
| Integral |
| Coupling Thickness: |
| 4.750 inches |
| Threaded After End: |
| Not included |
| |
| |

NSN 2010-00-352-0480 Ship Propulsion Shaft - Page 2 of 2



| Forward Bearing Sleeve Outside Diameter: |
|---|
| 25.000 inches |
| Forward Bearing Sleeve Length: |
| 6.792 feet |
| After Bearing Sleeve Outside Diameter: |
| 25.000 inches |
| After Bearing Sleeve Length: |
| 8.750 feet |
| Covering Location: |
| Surfaces between bearing sleeve covered |
| Forward End Taper Major Diameter: |
| 23.000 inches |
| Forward End Taper: |
| 0.125 per foot in inches |
| Material: |
| Steel, mil-s-890 |
| Material: |
| Steel |
| Material Specification: |
| Mil-s-890 military specification single material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T08000 |
| Mil-std (military Standard): |
| Mil-s-890 spec. |
| |